





## V2000BB BB type TRV Body

### RADIATOR VALVE WITH BROADBAND CARTRIDGE


#### PRODUCT DATA




Angle to DIN




Straight to DIN




Angle to NF




Straight to NF




Horizontal angle




Straight with swanneck



Corner angle



Horizontal angle (return)



Straight (return)

#### Application

Thermostatic radiator valve bodies (TRV bodies) are fitted on the supply or return of radiators or heat exchangers. Together with a radiator thermostat, for example the Thera-4, they control the room temperature by regulating the flow of hot water into the radiator. The temperature of different rooms is controlled individually and energy is saved.

TRV bodies of this type have quiet operation and are fitted to the supply or return of radiators on two-pipe systems with medium flow rates.

The valve insert can be replaced while the system is running and without draining using the service tool (see 'Accessories').

TRV bodies of this type are suitable for

- Honeywell radiator thermostats with M30 x 1.5 connection
- Certain Honeywell MT4 actuators
- Honeywell Hometronic HR80 and Roomtronic HR40 actuators

#### AT-Concept

AT-Concept valves share the same valve housing design. The valve insert can be replaced by any other AT-Concept valve insert, i.e. BB, KV, UBG, SL, VS, FS, FV and SC.

#### Features

- For heating systems with medium flow rates
- Available for installation on the supply or on the return
- Quiet operation
- DIN type bodies with dimensions according to EN215, Appendix A, Series D
- NF type bodies with dimensions according to EN215, Appendix A, Series F
- AT-Concept valve housing and insert
- Valve insert can be replaced while system is operating and without draining the system
- Valve opening spring is not in the water
- Standard M30 x 1.5 thermostat connection
- Supplied with black protection cap, imprinted 'BB' for clear identification

## Design

The thermostatic radiator valve body consists of:

- Valve housing PN10, DN10, 15 or 20 with
  - internal thread connection to DIN2999 (ISO7) for threaded, copper or precision steel pipe on inlet<sup>1</sup> (compression ring fittings see 'Accessories')
  - external thread connection with union-nut and radiator tail-piece on outlet<sup>1</sup> (Eurocone for DN15)
  - angle to DIN and straight to DIN bodies with dimensions according to EN215, Appendix A, Series D
  - angle to NF and straight to NF bodies with dimensions according to EN215, Appendix A, Series F
- Valve insert with BB (broadband) type cartridge
- Protection cap
- Union-nut and radiator tailpiece

NOTE: Vice versa for return type valve bodies.

## Materials

- Angle/straight to DIN, horizontal angle (return) and straight (return): valve housings made of nickel-plated red bronze
- Compact angle/straight, angle/straight to NF, corner angle, horizontal angle and swanneck tailpiece: valve housing made of nickel-plated hot-forged brass
- Valve insert made of brass with EPDM O-rings and soft seals and stainless steel spindle
- Protection cap made of black plastic
- Union-nut and tailpiece made of nickel-plated brass

### Please Note:

- To avoid stone deposit and corrosion the composition of the medium should conform with VDI-Guideline 2035
- Additives have to be suitable for EPDM sealings
- System has to be flushed thoroughly before initial operation with all valves fully open
- Any complaints or costs resulting from non-compliance with above rules will not be accepted by Honeywell
- Please contact us if you should have any special requirements or needs

## Installation Examples




Fig. 1. Angle




Fig. 2. Straight




Fig. 3. Horizontal angle




Fig. 4. Corner angle




Fig. 5. Straight with swanneck

## Specifications

<b>Medium</b>	Heating water, water quality to VDI2035
<b>Operating temperature</b>	max. 130°C (266°F)
<b>Operating pressure</b>	PN10
<b>Differential pressure</b>	max. 1 bar (14.5 psi) – max. 0.2 bar (2.9 psi) recommended for quiet operation
<b>k<sub>v</sub>(cv)-value</b>	0.62 (0.73)
<b>Nominal flow</b>	142 kg/h
<b>Thermostat connection</b>	M30 x 1.5
<b>Closing dimension</b>	11.5 mm
<b>Stroke</b>	2.5 mm

## Identification

- Black protection cap, 'BB' embossed on top of cap
- 'B' imprinted 3x on top of valve insert

## Function

Thermostatic radiator valves enable individual control of room temperature and thus save energy.

The TRV body is controlled by the radiator thermostat. Air from the room passing over the sensor of the radiator thermostat causes the sensor to expand when the temperature rises. The sensor acts onto the valve spindle and this causes the TRV body to close. When the temperature falls the sensor contracts and the spring-loaded valve spindle is opened. The TRV opens in proportion to the temperature of the sensor. Only the amount of water required to maintain the room temperature set on the radiator thermostat can flow into the radiator.

## Dimensions and Ordering Information




Fig. 6. Angle




Fig. 7. Straight




Fig. 8. Horizontal angle




Fig. 9. Corner angle




Fig. 10. Straight with swanneck

Table 1. Dimensions and OS-Nos (OS=Ordering System)


Body type	DN	EN215 certified	$k_{vs}(cv)$ -value	Pipe connection	I	L	h	H	h <sub>2</sub>	OS-No.
<b>For the supply</b>										
Angle to EN215 (D) (Fig. 6)	10	•	0.62 (0.73)	Rp 3/8"	26	52	22	20	—	V2000EBB10
	15	•	0.62 (0.73)	Rp 1/2"	29	58	26	20	—	V2000EBB15
	20	•	0.62 (0.73)	Rp 3/4"	34	66	29	19	—	V2000EBB20
Straight to EN215 (D) (Fig. 7)	10	•	0.62 (0.73)	Rp 3/8"	59	85	—	25	—	V2000DBB10
	15	•	0.62 (0.73)	Rp 1/2"	66	95	—	25	—	V2000DBB15
	20	•	0.62 (0.73)	Rp 3/4"	74	106	—	25	—	V2000DBB20
Angle to EN215 (F) (Fig. 6)	10	•	0.62 (0.73)	Rp 3/8"	24	49	20	21	—	V2020EBB10
	15	•	0.62 (0.73)	Rp 1/2"	26	53	23	22	—	V2020EBB15
	20	•	0.62 (0.73)	Rp 3/4"	34	66	29	18	—	V2020EBB20
Straight to EN215 (F) (Fig. 7)	10	•	0.62 (0.73)	Rp 3/8"	50	75	—	26	—	V2020DBB10
	15	•	0.62 (0.73)	Rp 1/2"	55	82	—	26	—	V2020DBB15
	20	•	0.62 (0.73)	Rp 3/4"	74	106	—	24	—	V2020DBB20
Horizontal angle (Fig. 8)	10	•	0.62 (0.73)	Rp 3/8"	24	50	22	33	—	V2000ABB10
	15	•	0.62 (0.73)	Rp 1/2"	26	54	26	35	—	V2000ABB15
Corner angle, radiator connection left (Fig. 9)	10	•	0.62 (0.73)	Rp 3/8"	24	53	26	22	26.5	V2000LBB10
	15	•	0.62 (0.73)	Rp 1/2"	24	53	26	26	30.5	V2000LBB15
Corner angle, radiator connection right (Fig. 9)	10	•	0.62 (0.73)	Rp 3/8"	24	53	26	22	26.5	V2000RBB10
	15	•	0.62 (0.73)	Rp 1/2"	24	53	26	26	30.5	V2000RBB15
Swanneck (Fig. 10)	15	•	0.62 (0.73)	Rp 1/2"	66	108	25	—	—	V2000BBB15
<b>For the return</b>										
Horizontal angle (Fig. 8)	10	•	0.62 (0.73)	Rp 3/8"	25	52	22	21	—	V2000HBB10
	15	•	0.62 (0.73)	Rp 1/2"	29	58	26	23	—	V2000HBB15
Straight (Fig. 7)	10	•	0.62 (0.73)	Rp 3/8"	57	85	—	23	—	V2000IBB10
	15	•	0.62 (0.73)	Rp 1/2"	65	95	—	23	—	V2000IBB15

NOTE: All dimensions in mm unless stated otherwise.

## Accessories



### Pipe Connections

#### Compression ring and nut



	3/8" x 10 mm	VA620A1010
	3/8" x 12 mm	VA620A1012
	1/2" x 10 mm	VA620A1510
	1/2" x 12 mm	VA620A1512
	1/2" x 14 mm	VA620A1514
	1/2" x 15 mm	VA620A1515
	1/2" x 16 mm	VA620A1516
	3/4" x 18 mm	VA620A2018
	3/4" x 22 mm	VA620A2022

NOTE: Support inserts have to be used for copper or soft steel pipe with 1.0 mm wall thickness


#### Compression ring and nut with support insert (2 pcs each)

	3/8" x 12 mm	VA621A1012
	1/2" x 12 mm	VA621A1512
	1/2" x 15 mm	VA621A1515
	1/2" x 16 mm	VA621A1516
	3/4" x 18 mm	VA621A2018


#### Compression ring and nut with support insert for composite pipe (2 pcs each)

	1/2" x 14 mm	VA622B1514
	1/2" x 16 mm	VA622B1516


#### Reduction piece

	1" pipe > 1/2" valve	VA6290A260
	1 1/4" pipe > 1/2" valve	VA6290A280
	1" pipe > 3/4" valve	VA6290A285
	1 1/4" pipe > 3/4" valve	VA6290A305


#### Radiator tailpiece with thread up to collar

	for valves DN10 (3/8")	VA5201A010
	for valves DN15 (1/2")	VA5201A015
	for valves DN20 (3/4")	VA5201A020

#### Extended radiator tailpiece, nickel-plated, to be shortened as required


	3/8" x 70 mm (for DN10) thread approx. 50 mm	VA5204B010
	1/2" x 76 mm (for DN15) thread approx. 65 mm	VA5204B015
	3/4" x 70 mm (for DN20) thread approx. 60 mm	VA5204B020

#### Soldering tailpiece


	3/8" x 12 mm (for DN10)	VA5230A010
	1/2" x 15 mm (for DN15)	VA5230A015
	3/4" x 22 mm (for DN20)	VA5230A020

## Valve Accessories


### Manual handwheel cap

	Pre-settable, with integrated locking device	VA2200D001
---	--	------------


### Pressure cap – for shutting off valves on radiator outlet

	for valves DN10 (3/8")	VA2202A010
	for valves DN15 (1/2")	VA2202A015
	for valves DN20 (3/4")	VA2202A020

### Sealing ring for pressure cap

	for valves DN10 (3/8")	VA5090A010
	for valves DN15 (1/2")	VA5090A015
	for valves DN20 (3/4")	VA5090A020


### Service tool to replace valve insert

	for all sizes	VA8200A001
---	---------------	------------

### Replacement valve insert

	BB type	VS1200BB01
---	---------	------------

## Flow Diagram



P-Band	1K	2K	3K	open = kvs
k <sub>v</sub> -value	0.22	0.45	0.52	0.62
cv-value	0.26	0.53	0.61	0.73

### Design Example

Given: Flow rate 150 kg/h  
 Required: Pressure loss ( $\Delta p$ ) with a P-band of 2K  
 Solution: The required pressure loss is found at the intersection of the flow line with the line for the chosen valve performance P=2K  
 Result:  $\Delta p = 110 \text{ mbar} = 11\,000 \text{ Pa}$

**Automation and Control Solutions**

Honeywell GmbH

Hardhofweg

74821 Mosbach, Germany

Phone: +49 (6261) 810

Fax: +49 (6261) 81393

[www.honeywell.com](http://www.honeywell.com)

EN0H-2100GE25 R0307  
March 2007

© 2007 Honeywell International Inc.  
Subject to change • All rights reserved

Manufactured for and on behalf of the Environmental and Combustion  
Controls Division of Honeywell Technologies Sàrl, Ecublens, Route  
du Bois 37, Switzerland or its authorized representative.

**Honeywell**